



environmental affairs

Department:
Environmental Affairs
REPUBLIC OF SOUTH AFRICA

RISK ASSESSMENT IN TERMS OF REGULATION 8 OF THE WASTE EXCLUSION REGULATIONS

APPLICANT	Hermic Ferrochrome (Pty) Ltd (in business rescue)
WASTE STREAM OR PORTION OF A WASTE STREAM	Waste Slag from Ferrochrome Metallurgy
BENEFICIAL USE/S	Use as aggregates
	Concrete aggregates
	Road base and covering and road stabilisation
	Asphaltic concrete and other bituminous mixtures
	Construction fill
	Concrete products

	Plaster and granite sands
	Railroad ballast
	Roofing granules
	Filtration media
	Pipe filling material
	Backfilling
	Dam construction and stabilisation material
	Construction of drainage systems
	Hydroponic filling material
	Production of cement
WASTE GENERATING FACILITY	
PHYSICAL ADDRESS OF FACILITY	R/E of Portion 103, De Kroon 444 JQ
	Brits 0250
GPS CO-ORDINATES OF WASTE GENERATING FACILITY	S25°39'45.76 E27°50'32.65

CONTACT PERSON	
NAME	Elzanne Moodie
ADDRESS	P.O.Box 4534 Brits 0250
EMAIL ADDRESS	Elzanne.moodie@hernic.co.za
TELEPHONE	0123811124
* DETAILED DESCRIPTION OF WASTE GENERATING PROCESS	<p>Ferrochrome is an essential ingredient for the production of stainless steel, and is an alloy of iron and chromium with a chromium content of between 50 and 55 percent. Stainless steel depends on chrome for its appearance and its resistance to corrosion.</p> <p>Ferrochrome production is essentially a carbothermic reduction operation taking place at high temperatures. The ore – an oxide of chromium and iron – is reduced by coal and coke to form an iron-chromium alloy called ferrochrome. The heat for this reaction comes from the electric arc formed between the tips of the electrodes in the bottom of the furnace and the furnace hearth. This arc creates temperatures of about 2 800°C.</p> <p>Tapping takes place intermittently. When enough smelted ferrochrome has accumulated in the hearth of the furnace, the tap hole is drilled open and a stream of molten metal and slag flows down a trough into a chill or ladle. The ferrochrome solidifies in large castings, while the slag is separated and stockpiled for further processing.</p> <p>The product is crushed and screened to exact customer specifications. Alternatively, the ferrochrome is granulated into a flowing stream of water.</p> <p>To improve total ferrochrome recovery while maintaining a high-quality product, alloy recovery plants are utilised to recover the ferrochrome from the slag produced during the charge chrome process. The slag, which has a metallic content of approximately 4 percent, is processed through a series of crushers and broken down to minus 15mm material. It then moves through a wet jigging plant where the chrome and slag are separated by means of gravity or magnets. The slag is then stockpiled into various size fractions for further use by external customers. Un-used slag is then disposed on a slag waste storage facility. The slag from these facilities is intended to be recovered for beneficial uses as listed above.</p>

PRODUCTION PROCESS FLOW CHART ATTACHED	YES ✓	NO
IDENTIFICATION OF HAZARDS	Not applicable	
WASTE CLASSIFICATION	HAZARDOUS	GENERAL
*A process flow chart must be attached to the process description		

RISK ASSESSEMENT WITHOUT MITIGATION

Activity	Risk Description	Environmental receptors	Impact	Assessment of the risk				
				Probability	Magnitude	Duration	Scale	Significance
Transporting of slag	Potential for slag to become air-borne during transportation	Surrounding environment - Air - Roads - Other road users	Deterioration of air quality Damage to other vehicles	2	2	1	3	12 - low
Handling of slag	Potential for slag to emit dust during the loading and offloading of the slag	Air	Deterioration of local air quality	2	2	1	1	8 - low

Activity	Risk Description	Environmental receptors	Impact	Assessment of the risk				
				Probability	Magnitude	Duration	Scale	Significance
Material storage	Potential for stockpiled material to enter the surrounding environment	Soil (primary) Surface water (secondary)	Slag spillage on soil Slag spillage in water causing siltation	3	2	1	1	12 – low
Material handling and processing	Potential for slag to emit dust during handling, crushing and screening activities	Air	Deterioration of air quality	2	4	2	1	14 – low
Material handling and processing of slag	Potential for skin exposure of humans whilst working with slag	Health - skin	Potential for skin irritation and abrasion	4	2	1	1	16– low

Activity	Risk Description	Environmental receptors	Impact	Assessment of the risk				
				Probability	Magnitude	Duration	Scale	Significance
Material handling and processing of slag	Potential for eye contact exposure of humans whilst working with slag	Health - eye	Potential for eye irritation and abrasion	4	2	1	1	16- low
Material handling and processing of slag	Potential for inhalation of dust exposure of humans whilst working with slag	Health – respiratory system	Potential for respiratory irritation	4	2	1	1	16- low

Activity	Risk Description	Environmental receptors	Impact	Assessment of the risk				
				Probability	Magnitude	Duration	Scale	Significance
Material handling and processing of slag	Potential for ingestion of slag dust by humans whilst working with slag	Health	Potential for irritation	2	2	1	1	8 – low
Environmental spillage	Potential for accidental release of slag into the environment during transport and material handling	Soil, surface water.	Minor localised silt contamination Visual impacts	1	2	1	1	4 – low

The following factors and criteria must be used to assess the impacts of the activities:

Criteria	
MAGNITUDE (Severity)	DURATION
10 - Very high	5 - Permanent (longer than 10 years)
8 - High	4 - Long-term (5 to 10 years)
6 - Moderate	3 - Medium-term (12 months to 5 years)
4 - Low	2 - Short-term (0 to 12 months)
2 - Minor	1 - Immediate
SCALE	PROBABILITY (Likelihood)
5 - International	5 - Definite
4 - National	4 - Highly probable
3 - Regional	3 - Medium probability
2 - Local	2 - Low probability
1 - Site only	1 - Improbable
0 - None	0 - None

Magnitude

Magnitude measures the size of the impact

Duration

Duration refers to the lifetime of the impact i.e. how long it will last

Scale

The scale refers to the extent of the impact.

Probability

The probability refers to the chance of impact to occur. The potential impact could be most likely to occur, unlikely, etc.

Assessment of Significance of impact

Significance rating of the potential impacts illustrates the importance of the impact itself. The size of area affected by pollution may be extremely high but the significance of this effect is dependent on the concentration or level of pollution in that area. In order to determine the significance of impact, the following method was used:

$$\text{Significance Points (SP)} = (\text{Magnitude} + \text{Duration} + \text{Scale}) \times \text{Probability}$$

The values of SP are then ranged as follows:

Rating	Description
SP >60	An impact which could influence the decision about whether or not to proceed with the activities regardless of any possible mitigation.
SP 30 – 60	An impact or benefit which is sufficiently important to require management and which could have an influence on the decision unless it is mitigated.
SP <30	Impacts with little real effect and which will not have an influence on or require modification of the activities.
+	An impact that is likely to result in positive consequences/effects

I, Elzanne Moodie hereby declare that I have read the completed the Risk Assessment form and hereby confirm that the information is to the best of my knowledge true and correct.

Furthermore, I declare that I am fully aware of my responsibilities in terms of the Waste Exclusion Regulations, and that failure to comply with these Regulations may constitute an offence in terms of the National Environmental Management: Waste Act, 2008 (Act 59 of 2008).

Applicant (Full names) Elzanne Moodie

Designation Head: Safety and Sustainable Development

Signature 

Date 27/01/2018 Place Fortis

FOR OFFICE USE ONLY

Date Received			
Decision Taken	Authorised	Not Authorised(provide reasons)	
Reference Number			

CONTACT PERSON	
NAME	Elzanne Moodie
ADDRESS	P.O.Box 4534 Brits 0250
EMAIL ADDRESS	Elzanne.moodie@hemic.co.za
TELEPHONE	0123811124
* DETAILED DESCRIPTION OF WASTE GENERATING PROCESS	<p>Ferrochrome is an essential ingredient for the production of stainless steel, and is an alloy of iron and chromium with a chromium content of between 50 and 55 percent. Stainless steel depends on chrome for its appearance and its resistance to corrosion.</p> <p>Ferrochrome production is essentially a carbothermic reduction operation taking place at high temperatures. The ore – an oxide of chromium and iron – is reduced by coal and coke to form an iron-chromium alloy called ferrochrome. The heat for this reaction comes from the electric arc formed between the tips of the electrodes in the bottom of the furnace and the furnace hearth. This arc creates temperatures of about 2 800 °C.</p> <p>Tapping takes place intermittently. When enough smelted ferrochrome has accumulated in the hearth of the furnace, the tap hole is drilled open and a stream of molten metal and slag flows down a trough into a chill or ladle. The ferrochrome solidifies in large castings, while the slag is separated and stockpiled for further processing.</p> <p>The product is crushed and screened to exact customer specifications. Alternatively, the ferrochrome is granulated into a flowing stream of water.</p> <p>To improve total ferrochrome recovery while maintaining a high-quality product, alloy recovery plants are utilised to recover the ferrochrome from the slag produced during the charge chrome process. The slag, which has a metallic content of approximately 4 percent, is processed through a series of crushers and broken down to minus 15mm material. It then moves through a wet jigging plant where the chrome and slag are separated by means of gravity or magnets. The slag is then stockpiled into various size fractions for further use by external customers. Un-used slag is then disposed on a slag waste storage facility. The slag from these facilities is intended to be recovered for beneficial uses as listed above.</p>