

environmental affairs

Department: Environmental Affairs **REPUBLIC OF SOUTH AFRICA**

RISK ASSESSMENT IN TERMS OF REGULATION 8 OF THE WASTE

EXCLUSION REGULATIONS

APPLICANT	Middelburg Ferrochrome, a business unit of Samancor Chrome Limited
WASTE STREAM OR PORTION OF A WASTE STREAM	Ferrochrome slag
BENEFICIAL USE/S	Use as aggregates
	Concrete aggregates
	Road base and covering and road stabilisation
Asphaltic concrete and other bituminous mixtures	
	Construction fill
	Concrete products

	Plaster and granite sands					
	Railroad ballast					
	Roofing granules					
	Filtration media					
	Pipe filling material					
	Backfilling					
	Dam construction and stabilisation material					
	Construction of drainage systems					
	Hydroponic filling material					
	Production of cement					
WASTE GENERATING FACILITY						
PHYSICAL ADDRESS OF FACILITY	Off Hendrina road					
	Middelburg, MP					
GPS CO-ORDINATES OF WASTE	Corners Latitude Longitude					
GENERATING FACILITY	1 -25.80769 29.49341					

	2	-25.81025	29.49677			
	3	-25.81469	29.49711			
	4	-25.81438	29.49119			
	5	-25.81163	29.49205			
	6	-25.80866	29.49118			
CONTACT PERSON						
NAME	Heather Booy	rsen				
ADDRESS	1st Floor, Block B, Cullinan Place, Cullinan Close (off Rivonia Road), Morningside					
EMAIL ADDRESS	heather.booysen@samancorcr.com					
TELEPHONE	0132494407					
* DETAILED DESCRIPTION OF WASTE GENERATING PROCESS	Ferrochrome is an essential ingredient for the production of stainless steel, and is an alloy of iron and chromium with a chromium content of between 50 and 55 percent. Stainless steel depends on chrome for its appearance and its resistance to corrosion. Ferrochrome production is essentially a carbothermic reduction operation taking place at high temperatures. The ore – an oxide of chromium and iron – is reduced by coal and coke to form an iron-chromium alloy called ferrochrome. The heat for this reaction comes from the electric arc formed between the tips of the electrodes in the bottom of the furnace and the furnace hearth. This arc creates temperatures of about 2 800°C.					
	Tapping takes place intermittently. When enough smelted ferrochrome has accumulated in the hearth of the furnace, the tap hole is drilled open and a stream of molten metal and slag flows down a trough into a chill or ladle. The ferrochrome solidifies in large castings, while the slag is separated and stockpiled for further processing.					

		X			
WASTE CLASSIFICATION	HAZARDOUS	GENERAL			
IDENTIFICATION OF HAZARDS	Not applicable				
PRODUCTION PROCESS FLOW CHART ATTACHED	YES 🗸	NO			
	 The product is crushed and screened to exact customer specifications. Alternatively, the ferrochrome is granulated into a flowing stream of water. To improve total ferrochrome recovery while maintaining a high-quality product, alloy recovery plants are utilised to recover the ferrochrome from the slag produced during the charge chrome process. The slag, which has a metallic content of approximately 4 percent, is processed through a series of crushers and broken down to minus 15mm material. It then moves through a wet jigging plant where the chrome and slag are separated by means of gravity or magnets. The slag is then stockpiled into various size fractions for further use by external customers. 				

RISK ASSESSEMENT WITHOUT MITIGATION

Activity	ctivity Risk Envi Description		Impact	Assessment of the risk				
	Description			Probability	Magnitude	Duration	Scale	Significance
Transporting of slag	Potential for slag to become air-	Surrounding environment - Air - Roads	Deterioration of air quality	2	2	1	3	12 - low

Activity	Risk	Environmental receptors	Impact		Asses	sment of th	ne risk	
	Description			Probability	Magnitude	Duration	Scale	Significance
	borne during transportation	- Other road users	Damage to other vehicles					
Handling of slag	Potential for slag to emit dust during the loading and offloading of the slag	Air	Deterioration of local air quality	2	2	1	1	8 - low
Material storage	Potential for stockpiled material to enter the surrounding environment	Soil (primary) Surface water (secondary)	Slag spillage on soil Slag spillage in water causing siltation	3	2	1	1	12 – Iow
Material handling and processing	Potential for slag to emit dust during handling, crushing and screening activities	Air	Deterioration of air quality	2	4	2	1	14 – Iow

Activity	Risk	Environmental receptors	Impact		Assessment of the risk					
	Description			Probability	Magnitude	Duration	Scale	Significance		
Material handling and processing of slag	Potential for skin exposure of humans whilst working with slag	Health - skin	Potential for skin irritation and abrasion	4	2	1	1	16– Iow		
Material handling and processing of slag	Potential for eye contact exposure of humans whilst working with slag	Health - eye	Potential for eye irritation and abrasion	4	2	1	1	16– low		

Activity	Risk	Environmental receptors	Impact	Assessment of the risk				
	Description			Probability	Magnitude	Duration	Scale	Significance
Material handling and processing of slag	Potential for inhalation of dust exposure of humans whilst working with slag	Health – respiratory system	Potential for respiratory irritation	4	2	1	1	16– low
Material handling and processing of slag	Potential for ingestion of slag dust by humans whilst working with slag	Health	Potential for irritation	2	2	1	1	8 – Iow
Environmental spillage	Potential for accidental release of slag into the environment	Soil, surface water.	Minor localised silt contamination Visual impacts	1	2	1	1	4 – Iow

Activity Risk	Risk Description		Impact	Assessment of the risk				
	Description			Probability	Magnitude	Duration	Scale	Significance
	during transport and material handling							

The following factors and criteria must be used to assess the impacts of the activities:

Criteria				
MAGNITUDE (Severity)	DURATION			
10 - Very high	5 – Permanent (longer than 10 years)			
8 – High	4 - Long-term (5 to 10 years)			
6 – Moderate	3 - Medium-term (12 months to 5 years)			
4 – Low	2 - Short-term (0 to 12 months)			
2 – Minor	1 – Immediate			
SCALE	PROBABILITY (Likelihood)			
5 – International	5 - Definite			
4 – National	4 - Highly probable			
3 – Regional	3 - Medium probability			
2 – Local	2 - Low probability			
1 - Site only	1 – Improbable			
0 – None	0 – None			

Magnitude

Magnitude measures the size of the impact

Duration

Duration refers to the lifetime of the impact i.e. how long it will last

Scale

The scale refers to the extent of the impact.

Probability

The probability refers to the chance of impact to occur. The potential impact could be most likely to occur, unlikely, etc.

Assessment of Significance of impact

Significance rating of the potential impacts illustrates the importance of the impact itself. The size of area affected by pollution may be extremely high but the significance of this effect is dependent on the concentration or level of pollution in that area. In order to determine the significance of impact, the following method was used:

Significance Points (SP) = (Magnitude + Duration + Scale) x Probability

The values of SP are then ranged as follows:

	Rating	Description
SP >60	Indicates high environmental significance	An impact which could influence the decision about whether or not to proceed with the activities regardless of any possible mitigation.
SP 30 – 60	Indicates moderate environmental significance	An impact or benefit which is sufficiently important to require management and which could have an influence on the decision unless it is mitigated.
SP <30	Indicates low environmental significance	Impacts with little real effect and which will not have an influence on or require modification of the activities.
+	Positive impact	An impact that is likely to result in positive consequences/effects

Furthermore, I declare that I am fully aware of my responsibilities in terms of the Waste Exclusion Regulations, and that failure to comply with these Regulations may constitute an offence in terms of the National Environmental Management: Waste Act, 2008 (Act 59 of 2008).	I,— hereby declare that I have read the co information is to the best of my knowledge true and correct.	mpleted the Risk Assessment form and hereby confirm that the				
Designation	Applicant (Full names)					
Designation	Designation —					
Signature	Signature ———	-				
Date — Place — Place —	Date — Place — Place —					

FOR OFFICE USE ONLY				
Date Received				
Decision Taken	Authorised	Not Authorised(provide reasons)		
Reference Number				

Page 11 of 11