



**forestry, fisheries
& the environment**

Department:
Forestry, Fisheries and the Environment
REPUBLIC OF SOUTH AFRICA

**RISK MANAGEMENT PLAN IN TERMS OF REGULATION 10 OF THE
WASTE EXCLUSION REGULATIONS**

	(For official use only)
File Reference Number:	12/9/11
NEAS Reference Number:	
Date Received:	

Risk Assessment for an application for exclusion of waste stream or portion of waste stream in terms of the National Environmental Management: Waste Act, 2008(Act No.59 of 2008), as amended.

Kindly note that:

1. This form is current as of 01 April 2021. It is the responsibility of the applicant to ascertain whether subsequent versions of the form have been published or produced by the competent authority.
2. The information must be typed within the spaces provided in the form. The sizes of the spaces provided are not necessarily indicative of the amount of information to be provided. Spaces are provided in tabular format and will extend automatically when each space is filled with typing.
3. Incomplete forms (including information as required in the application form may be returned to the applicant for revision and the inclusion of additional information.
4. Unless protected by law, all information filled in on this application will become public information on receipt by the competent authority. Any interested and affected party should be provided with the information contained in this application on request, during any stage of the application process.

BACKGROUND INFORMATION						
Applicant	Illovo Sugar (South Africa) (Pty) Ltd – Eston Sugar Mill					
Contact Person	Country SHERQ Manager					
Name	Shaun Ramsunder					
Address	PO Box 194, Durban, South Africa, 4000					
E-Mail Address	SRamsunder@ilovo.co.za					
Telephone	031 508 4591					
Cell Phone	084 554 9664					
WASTE FACILITY OR FACILITIES						
Source (s) of waste	Bagasse, wood, coal are used as fuel sources in the boiler.					
Waste to be beneficiated	Boiler ash					
Gps co-ordinates at corners of waste generating facility or facilities <i>(Please note that the co - ordinates are of the Boiler)</i>	LATITUDE			LONGITUDE		
	29°	52'	14.25"S	30°	31'	45.59"E
	29°	52'	14.30"S	30°	31'	45.89"E
	29°	52'	14.62"S	30°	31'	45.79"E
	29°	52'	14.54"S	30°	31'	45.50"E
Beneficial use/s	Soil enhancer on sugar cane farms and blockmaking					
WASTE GENERATING PROCESS						
MSDS attached if hazardous	YES ✓ Please refer to Annexue 1			NO		
Waste generating facility	HAZARDOUS ✓			GENERAL		

RISK MANAGEMENT PLAN

Refer to the SDS, for specific management tools for safety, health and environmental management in case of exposures, and emergencies.

Activity	Risk Description	Action(s) to minimise/manage the risk	Responsibility (Who is responsible to carry out the action(s))
<p>Context Eston Mill has on their SHEQ system:</p> <ul style="list-style-type: none"> - Pollution risk control document, - Waste management document. • The classification and the SSV comparison of the boiler ash gives very good indications of the hazards encountered by all affected stakeholders when working with ash. It helps to identify areas which must be managed in order to minimise or eliminate risks. The intention is to maximize the intended beneficial use of the waste, while minimising any unacceptable impacts to people, environment and economic harm. • Reference MUST be made to the Safety Data Sheet (SDS) in the assessment and management of all risks. 		<ul style="list-style-type: none"> • Each party i.e. the generator, driver/owner, and recipient of the ash/mixture, is to have the latest, legal copy of the safety data sheet. • Training must be done for the contents and understanding of the contents for all relevant stakeholders. • Eston Mill must incorporate the safety data sheet into the waste management system, emergency management systems, and contents into the work instructions, together with training and include these into the induction program. 	<p>The Eston mill staff will be responsible for the handling, transporting, storing, or working with the boiler ash and the ash/filter cake mixture waste stream. The staff are to be made aware of the safety data sheet, its contents and where to obtain it.</p>

Ash/mixture removal.	Storage over a long time and running out of storage space, if demand is low.	<ul style="list-style-type: none"> • The monitoring of the ash/mixture demand must match the amount of ash/mixture that is stored on the platform in the mill. This must not build up and cause an overflow into the sludge dam. Should there be circumstances that would reduce the removal rate of the ash/mixture then the sludge dam level must be closely monitored to ensure this facility does not overflow. • The tractor trailer must be maintained to prevent any break-downs and down-time. • The farmer's demand for the product would be co-ordinated with the season that the fertilization of the fields is happening and hence be coordinated with the supply, to prevent build-up of the material. 	<ul style="list-style-type: none"> • Manager in charge of the storage area for the ash/mixture. • SHEQ manager.
Access to ash/mixture storage area	<p>Security:</p> <ul style="list-style-type: none"> • Unauthorised access to ash area and • unauthorised removal of ash. 	<ul style="list-style-type: none"> • Retain security and access control at the gates. • Checking for correct PPE. • Site induction covers the safety and health risks and requirements for entering the site. Induction to be renewed every year. • The SDS is to be given to each farmer and worker. • Works instructions to include the vehicle checks. 	Eston Mill gate security
Process of transferring ash/mixture from the bunded area to the receiving vehicles.	<ul style="list-style-type: none"> • Dust: Windblown from the process of ash transfer with front end loader. • Spillage: onto area outside of bunded area. • Hot ash: The quenched ash still being too hot after coming from the boilers. 	<ul style="list-style-type: none"> • Keep the ash moist to reduce the ash from being blown by the wind. This can be part of the ash quenching process. • Place a tarp over the waste ash/mixture when fully loaded to prevent windblown ash on the road. • Ensure the ash temperature is safe for handling for mixing with the filter cake and for loading onto the vehicles. • Ensure that only the responsible personnel needed for the activity are in the area for the duration of the transfer. • Ensure correct PPE is used in the area as per SDS. Eye protection, gloves, appropriate clothing footwear and respiratory protection is worn that is appropriate to the dust that may be generated. Eye wash station to be clearly demarcated and close by. • Careful management of the transfer of ash/mixture to vehicles. • Procedure very clear for limit of vehicle load, to minimise on-site and off-site spillage. • Clean-up of storage area with each batch of ash/mixture. 	Manager responsible for waste and operations.

		<ul style="list-style-type: none"> • Ensure the area is cleaned at the end of the working day to minimise the chance of any oil grease or other materials to contaminate the mixture. 	
Process of mixing the ash with the filter on mill site.	Dust and spillage from the mixing process of ash with filter cake.	<ul style="list-style-type: none"> • Ensure correct PPE is used as is appropriate for the level of ash dust and to prevent filter cake/ash mixture to be splashed onto the hands, skin, face and eyes. • Minimize wastage and spillage to reduce or eliminate any spillage into the sludge dams. 	Waste manager and operator that performs the mixing activity.
Transporting of ash/mixture by tractor and trailer to farm.	<p>Spillage:</p> <ul style="list-style-type: none"> • Overfilling receiving vehicle with ash/mixture. • Windblown ash. • Road accidents causing spillages on the main roads.. • Non –compliance to the Road Traffic Act (RTA) • Soil contamination. • Affects the flora and local animals, domestic and wild. • Natural water sources contamination. 	<ul style="list-style-type: none"> • Ensure the driver is trained in the contents of the SDS and appropriate actions needed should an emergency arise. • Ensure vehicles are well maintained with service records available. • The condition of the vehicle is to be monitored by the on site garage to include regular maintenance, driver reports for any concerns on the vehicle performance, security gate personnel to check the vehicle condition when entering the gate. • Should there be any incident on the public road or on farm roads, an enquiry is to take place, to investigate whether any actions are to take place against driver. • Illovo Eston mill contact number must be clearly visible by outside persons for reporting of driver conduct • Procedure for off-loading of ash/mixture in the designated drop-off zones. The protocol to ensure the off-loading vehicle driver knows the process for minimising the impact of the vehicle on the environment after completing the off-loading. • Driver to contact mill to clear up any spillages that occur on public roads. • Have a hotline for public complaints for ash spillage and nuisance and register these on the SHE system. Address these with the responsible owner/driver and train the driver again. • Regular training and tool-box talks for the drivers of vehicles. • Emergency procedures clearly outlined with issuing of the SDS in the implications of accidents and clean-up. • Clean-up protocols sufficient for clean-up to deal with the maximum loads. Including clean-ups, barriers, fires, injuries, etc. All outlined in the correct and updated SDS. 	Eston mill vehicle manager, driver supervisor and driver, security.

		<ul style="list-style-type: none"> • Checks for correct driver emergency equipment and training to deal with the emergency. • Keep ash moist and ensure the tarp over the ash is secured. 	
Vehicle ash/mixture off-loading	<p>Spillage:</p> <ul style="list-style-type: none"> • Outside of dedicated area. • The vehicle used to offload may drop residual mixture when travelling to other places to do work. 	<ul style="list-style-type: none"> • Ensure that the ash/mixture is still moist to reduce the potential of windblown dust nuisance. • Any ash/mixture run-off is not towards any natural water source. This can be prevented by ensuring the riparian zone on the water course is intact. • The protocol for spreading onto the soils would be the same as any commercial fertilizer and lime additives to the soil management. • Ensure correct and appropriate PPE is used. Eye wash bottles to be available on the off-loading vehicle. • From a cradle to grave perspective the Mill would be responsible to ensure that no such fertiliser is offloaded or spilled in non-designated areas e.g. National road or entry point intersections or traverse areas. 	Eston mill agriculture - MCP and user of the ash/mixture.
Storage at end user facilities	<ul style="list-style-type: none"> • Water run off from fields with ash after rain, • Possible windblown dust if mixture is allowed to dry. 	As given above for off-loading protocols to prevent run-off contamination of natural water sources.	Farmer.
Ash/mixture management during distribution onto the intended farm soil as the fertilizer/soil enhancer.	<p>Dust:</p> <ul style="list-style-type: none"> • Health. There may be health impacts from working with the possibly dried ash/mixture during the spreading of fertilizer operations. • Environment: Any mixture slurry which may run-off from the mixture spreading operations will affect the receiving environment if not 	<ul style="list-style-type: none"> • All staff in the field are to be supplied with the correct PPE , • Trained for application rates of the ash/mixture, • Correct placement within the area of the field away from the possibility of run-off to cause pollution in the natural water sources. • The same protocols would apply as to application of commercial fertilizer onto the fields. • The Out grower and MCP client designates a loading zone which the filter cake is off-loaded routinely each day, the grower in turns distributes over their land at their own discretion 	Farmer - property owner and field staff with field supervisors.

	managed correctly, especially near to natural water sources.		
Repeat application onto the same fields.	Environment: The soils may have salinity build up if the soils are not monitored	Ensure that the work is conducted with the inputs of a qualified agronomist that the soil viability is retained. This prevents salinity build up and correct pH management, as well as other specific soil requirements to keep the crop healthy.	Farmer, property owner and field staff.
Secondary waste generation	Environment: Secondary waste generation would involve ash/mixture with a multitude of other items like oils, grease, as well as other items if the storage sites are not managed.	<ul style="list-style-type: none"> • The management of the ash/mixture platform includes the monitoring of any oil, grease, other waste stream spillages that may contaminate the ash and filter cake waste, thus rendering them unusable on the farm field. • Should there be a spill on this area, to immediately isolate the spill and to clean it up, together with the contaminated ash, filter cake and ash/mixture as per the systems and SDS procedures. • These contaminated streams are to be isolated and managed for disposal as per SHEQ protocol. • Disposal is to be safe and legal. 	Eston mill waste manager and SHEQ manager.
Emergency responders		<ul style="list-style-type: none"> • The SDS must be made available to these personnel, to be able to understand the requirements for their own protection and the management of any spill. • the drivers of the vehicles too, are to be trained in how to respond safely to any incident involving the load and who to contact in the case of any emergency. • The driver must know the protocol to manage the incident: and who to contact: Owner, emergency responders – fire, and medical. First aid skill, as required at the level of the driver too. 	Eston mill waste manager and SHEQ manager affected staff:

I, S. Raminder (the Applicant) hereby declare that I have read the completed Risk Management Plan form and hereby confirm that the information is, to the best of my knowledge, true and correct

Furthermore, I declare that I am fully aware of my responsibilities in terms of the Waste Exclusion Regulations, and that failure to comply with these Regulations may constitute an offence in terms of the National Environmental Management: Waste Act, 2008 (Act 59 of 2008).

[Signature]

Signature of the applicant¹/ Signature on behalf of the applicant:

SHARAD RAMSUNDER

Name of Applicant:

COUNTRY SHERA

Designation

17/05/2023

Date:

¹ If the applicant is a juristic person, a signature on behalf of the applicant is required as well as proof of such authority.

Annexure 1:

Safety Data Sheet

Safety Data Sheet

Waste handling and transport, RSA. No OELs / BLVs.

by: **TALBOT**
talbot.co.za | talbot@talbot.co.za 

Conforms to SANS 10234:2019, SANS 11014:2010
SDS compiled: 2022/09/29. Valid until: 2027/09/28
unless the applicable substance or mixture is altered
Version: 1

SDS Compiler v20.09.10.05.1

WASTE MIXTURE: SOLID
ILLOVO SUGAR - ESTON MILL: ASH

1. Identification

GHS product identifier

Trade name(s) : ILLOVO SUGAR - ESTON MILL: ASH

Supplier product code : No data available.

Other means of identification

Other synonym(s) : No data available.

Road & Rail PSN : NOT REGULATED

Relevant use(s) of the Mixture and restrictions on use

Identified use(s) : WASTE - intended for transport by road or rail, and disposal.

Uses advised against : WASTE - if a commercial product residue, not intended for original use. DO NOT eat, drink or smoke when using this product. AVOID release to the environment. Collect spillage.

Generator details

Generator name : Illovo Sugar South Africa (Pty) Ltd - Eston Mill

Generator address : District Rd R624,Eston, 3740

Contact title, name : Nancy Sutar

Phone number(s) : +27 (0) 83 504 3005

Alternative contact(s) : nsutar@illovo.co.za

Emergency contacts

Contact title, name : Nancy Sutar

Emergency number(s) : +27 (0) 83 504 3005

After-hours number(s) : +27 (0) 83 504 3005

2. Hazards identification

Classification of the Mixture per SANS 10234:2019

GHS hazard category : GHS hazard statements

- 2 : SKIN IRRITATION
- 1 : SERIOUS EYE DAMAGE

Hazards not otherwise classified : In the event that the waste is utilised in a manner that results in significant dust generation, potential health hazards may arise from dust exposure via inhalation. In the current form (wet ash), the waste is not expected to carry any significant inhalation hazards.

Inhalation (acute): Inhalation of dust may cause irritation to the respiratory tract and/or chest pain.

Inhalation (chronic): Repeated inhalation of dust containing respirable crystalline silica is associated with silicosis, lung cancer and autoimmune disorders. Long term exposure to aluminium oxide dust can lead to lung damage, long term exposure to iron oxide dust can lead to pneumoconiosis (siderosis) and long term exposure to titanium oxide dust can cause lung fibrosis (potential occupational carcinogen).

GHS hazard label elements

Symbol(s) :



Exclamation mark (GHS07)



Corrosive (GHS05)

Signal word : **DANGER**

GHS hazard statements

Physical

No data available.

Health

- H315 : Causes skin irritation
- H318 : Causes serious eye damage

Environmental

No data available.

Precautionary measures label elements

General

Prevention

- P261 : AVOID breathing dust, fume, gas, mist, vapours, spray.
- P262 : DO NOT get in eyes, on skin, or on clothing.
- P264 : Wash skin thoroughly after handling.
- P270 : DO NOT eat, drink or smoke when using this product.
- P273 : AVOID release to the environment.
- P280 : Wear protective gloves, protective clothing, eye protection, face protection.

Response

- P314 : Get medical advice / attention if you feel unwell.
- P374 : Fight fire with normal precautions from a reasonable distance.
- P391 : Collect spillage.
- P301+P312 : IF SWALLOWED: Call a POISON CENTRE or doctor /physician if you feel unwell.
- P302+P352 : IF ON SKIN: Wash with plenty of water.
- P304+P312 : IF INHALED: Call a POISON CENTRE or doctor/physician if you feel unwell.
- P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P311 : If exposed or concerned: Call a POISON CENTRE or doctor/physician.
- P362+P364 : Take off contaminated clothing and wash it before reuse.

Storage

Disposal

- P501 : Dispose of contents/container to an approved facility in accordance with all applicable regulations and landfill requirements per this safety data sheet's Section 13.

Other

3. Composition or information on ingredients

Substance/mixture : Mixture

Ingredient(s)	CAS/IUPAC/Other Name(s)	[C/I/SA] %	Classification (Regulation)
<u>Chemical Composition</u>			
Silicon dioxide (SiO ₂)	7631-86-9	72.26%[NS]	-
Iron oxide (Fe ₂ O ₃)	1309-37-1	11.24%[NS]	-
Aluminium oxide (Al ₂ O ₃)	1344-28-1	9.18%[NS]	-
Potassium oxide (K ₂ O)	12136-45-7	2.31%[NS]	H315 H318
Calcium oxide (CaO)	1305-78-8	1.89%[NS]	H315 H318
Magnesium oxide (MgO)	1309-48-4	0.98%[NS]	-
Sodium oxide (Na ₂ O)	1313-59-3	0.86%[NS]	H315 H318
Titanium dioxide (TiO ₂)	13463-67-7	0.46%[NS]	-
Phosphorous pentoxide (P ₂ O ₅)	1314-56-3	0.17%[NS]	H315 H318
<u>Mineral Composition</u>			
Quartz (SiO ₂)	14808-60-7	60%[NS]	-
Plagioclase ((Na,Ca)(Si,Al) ₄ O ₈)	68476-25-5	14%[NS]	-
Microcline (KAlSi ₃ O ₈)	-	12%[NS]	-
Enstatite (MgSiO ₃)	14681-78-8	10.8%[NS]	-
Augite ((Ca,Na)(Mg,Fe,Al)(Al,Si) ₂ O ₆)	-	1.8%[NS]	-
Muscovite (KAl ₂ (Si ₃ Al)O ₁₀ (OH,F) ₂)	12001-26-2	1.1%[NS]	-

Notes to above table: [C] Constituent component; [I] Impurity; [SA] Stabilising Additive; [NS] Not Specified; [O]

Hazardous ingredients : Refer to above table.
above cut-off levels

Additional information : 1. Elemental oxides were used to represent chemical composition and assist with hazard assignments.
2. Amorphous phases, if present, were not taken into consideration during quantification.
3. Mineral names may not reflect the actual compositions of minerals identified, but rather the mineral group. Ideal mineral formulae are represented above.

4. First-aid measures

Where the manufacturer/supplier/generator was unable to specify relevant measures, SANS 10234:2019 precautionary statements have been used.

Immediate actions : If exposed or concerned: Call a POISON CENTRE or doctor/physician.

Actions to be avoided : DO NOT eat, drink or smoke when using this product. AVOID release to the environment.

First-aid measures

Inhalation	: AVOID breathing dust, fume, gas, mist, vapours, spray. IF INHALED: Call a POISON CENTRE or doctor/physician if you feel unwell. Take off contaminated clothing and wash it before reuse.
Skin Contact	: DO NOT get in eyes, on skin, or on clothing. Wash skin thoroughly after handling. Wear protective gloves, protective clothing, eye protection, face protection. IF ON SKIN: Wash with plenty of water.
Eye Contact	: DO NOT get in eyes, on skin, or on clothing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Ingestion	: DO NOT get in eyes, on skin, or on clothing. IF SWALLOWED: Call a POISON CENTRE or doctor /physician if you feel unwell.

Anticipated effects and symptoms summaries - see Section 11 for full explanations

Acute effects	: On contact is expected to cause skin irritation and serious eye damage. Inhalation of dust may cause irritation to the respiratory tract.
Delayed effects	: Repeated exposure to dust can result in lung damage or disease.
Symptoms / effects	: No data available.

Protection of first-aiders and notes for attending physicians

First-aid protection	: No data available.
Physician notes	: Get medical advice / attention if you feel unwell.

5. Fire-fighting measures

Where the manufacturer/supplier/generator was unable to specify relevant measures, SANS 10234:2019 precautionary statements have been used.

Unsuitable extinguishing media	: No data available.
Extinguishing media and methods	: Use extinguishing media suitable to the surrounding fire.
Specific hazards arising from the Mixture	: No data available.
Protection of fire-fighters	: AVOID breathing dust, fume, gas, mist, vapours, spray. Fight fire with normal precautions from a reasonable distance.

6. Accidental release measures

Where the manufacturer/supplier/generator was unable to specify relevant measures, SANS 10234:2019 precautionary statements have been used.

Personal precautions, protective equipment, and emergency procedures : Wear protective gloves, protective clothing, eye protection, face protection.

Environmental precautions : AVOID release to the environment. Collect spillage.

Methods and materials for containment and for clean-up : Contain and collect as any solid. Avoid actions that cause dust to become airborne. Do not breathe dust, and do not allow large quantities of dust or wetted material to contact skin or eyes.

Secondary disaster prevention measures : No data available.

Additional information : No data available.

7. Handling and storage

Safe handling : DO NOT get in eyes, on skin, or on clothing. DO NOT eat, drink or smoke when using this product. AVOID release to the environment. Wear protective gloves, protective clothing, eye protection, face protection.

Safe storage : No data available.

Technical measures : No data available.

Incompatible materials : No data available.

Packaging : No data available.

Additional information : Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment, and wash hands after use and before entering eating areas.

8. Exposure controls and personal protection

Concentration and exposure limits

Permissible concentration : No data available.

Exposure controls and Personal Protective Equipment (PPE)

Engineered controls : Activities that generate dust require the use of general ventilation and/or wet suppression methods to maintain exposure.

- Respiratory PPE : Use respiratory protection approved under appropriate government standards.
- Hand / arm PPE : Handle with gloves approved under appropriate government standards.
- Eye / face PPE : Use equipment for eye protection tested and approved under appropriate government standards.
- Skin / body PPE : Wear protective clothing.
- Hygiene measures : Handle in accordance with good hygiene and safety practice. Wash hands before and after handling.

Special conditions posing a hazard

- Hazardous conditions : Avoid dust generation.
- Additional information : No data available.

9. Physical and chemical properties (whole waste mixture)

- Appearance : Damp, black pieces of ash
- Odour : Odourless
- Odour threshold : No data available.
- pH, concentration : 6.8
- Melting point : No data available.
- Freezing point : No data available.
- Initial boiling point : No data available.
- Boiling point : No data available.
- Boiling range : No data available.
- Flashpoint : No data available.
- Flammability : No data available.
- Auto-ignition point : No data available.
- Decomposition point : No data available.
- Lower explosion limit : No data available.
- Upper explosion limit : No data available.
- Vapour pressure : No data available.
- Evaporation rate : No data available.

Vapour density : No data available.
Density : No data available.
Bulk density : No data available.
Relative density, SG : No data available.
Solubility : No data available.
Partition coeff. (n-oct) : No data available.
Partition coeff. (water) : No data available.
Dynamic viscosity : No data available.
Kinematic viscosity : No data available.
Radioactivity : No data available.

10. Stability and reactivity

Conditions to avoid : Avoid dust generation.
Incompatible materials : No data available.
Hazardous decomposition : No data available.
Additional information : No data available.

11. Toxicological information

GHS Classification of Health Hazards

Acute toxicity : No data available.
Skin irritation/corrosion : Causes skin irritation
Eye damage/irritation : Causes serious eye damage
Respiratory or skin sensitization : No data available.
Germ cell mutagenicity : No data available.
Carcinogenicity : No data available.
Reproductive toxicity : No data available.
Specific target organ toxicity - single exp. : No data available.
Specific target organ : No data available.

toxicity - repeated exp.

Aspiration hazard : No data available.

Hazard	Ingredient	Result	Species	Dose	Time
Skin irritation	CaO, Na ₂ O, K ₂ O, P ₂ O ₅	H315(2)	-	-	-
Eye damage	CaO, Na ₂ O, K ₂ O, P ₂ O ₅	H318(1)	-	-	-

Additional information : Inhalation (acute): Inhalation of dust may cause irritation to the respiratory tract and/or chest pain.

Inhalation (chronic): Repeated inhalation of dust containing respirable crystalline silica is associated with silicosis, lung cancer and autoimmune disorders. Long term exposure to aluminium oxide dust can lead to lung damage, long term exposure to iron oxide dust can lead to pneumoconiosis (siderosis) and long term exposure to titanium oxide dust can cause lung fibrosis (potential occupational carcinogen).

12. Ecological information

GHS Classification of Aquatic Environment Hazards

Acute aquatic toxicity : No data available.

Chronic aquatic toxicity : No data available.

Hazard to the ozone layer : No data available.

Hazard	Ingredient	Result	Species	Dose	Time

Persistence and degradability : No data available.

Bioaccumulation potential : No data available.

Mobility in soil : No data available.

PBT, vPvB summary : No data available.

Other adverse effects : No data available.

Additional information : Generic hazard data used above.

13. Disposal considerations

Current disposal prohibition/restrictions	: No current prohibitions identified.
Landfill Class (RSA) (subject to treatment)	: Type 3 Waste: Class C Landfill (GLB+) per: GN R635 (7)(2)(d) - strictly subject to treatment due to GN R636 (5)(1) prohibited disposal: see above.
Future disposal prohibition/restrictions	: No future restrictions identified.
Safe, environmentally preferred disposal	: Dispose of contents/container to an approved facility in accordance with all applicable regulations and landfill requirements per this safety data sheet's Section 13.
Additional information	: Do not fly tip. Do not dispose into sewer, stormwater, or environment. Do not burn unless by means of compliant incineration practices.

14. Transport information

Proper Shipping Name (PSN) for: Road & Rail (SANS 10228) | Air (IATA) | Sea Freight (IMO/IMDG)

Road & Rail PSN	: NOT REGULATED
IATA PSN	: NOT REGULATED
IMO/IMDG PSN	: NOT REGULATED

Dangerous Goods Transportation: Road & Rail Requirements (SANS 10228:2012)

UN number	: -
Dangerous goods class (& Subsidiary)	: -
Packing group	: -
Special provisions	: -
Packaging codes	: -
Marine pollutant	: No data available.

Transport in bulk according to MARPOL 73/78 Annex II and the IBC Code

Regulation	: Not intended for sea freight.
Shipment approved	: Not intended for sea freight.
Pollution name	: Not intended for sea freight.
Pollution category	: Not intended for sea freight.
Ship type	: Not intended for sea freight.

Additional information

Additional information : No data available.

15. Regulatory information

Occupational H&S : Occupational Health and Safety Act (Act No. 85 of 1993)

Environment & Disposal : National Environmental Management: Waste Act (Act No. 59 of 2008)
: GN R634 Waste Classification and Management Regulations
: GN R635 National Norms & Standards for the Assessment of Waste for Landfill Disposal
: GN R636 National Norms and Standards for Disposal of Waste to Landfill

Other (domestic) : National Road Traffic Act, 1996 (Act No. 93 of 1996)

Other (international) : No data available.

Classification & Hazard communication : SANS 10228:2012 The identification and classification of dangerous goods for transport by road and rail modes
: SANS 10234:2008 List of classification and labelling of chemicals in accordance with the Globally Harmonized System (GHS)
: SANS 10234:2019 Globally Harmonized System of classification and labelling of chemicals (GHS)

16. Other information

Compilation & version : 2022/09/29, Version: 1, Revision: -

Revision(s) : Not applicable

Summary of Mixture Hazard Classification and Categories

2 : SKIN IRRITATION
1 : SERIOUS EYE DAMAGE

Summary of Mixture Hazard Statements

H315 : Causes skin irritation
H318 : Causes serious eye damage

Signal word : **DANGER**

Other : No data available.

Disclaimer & Use

This Safety Data Sheet (SDS) has been prepared based on information provided to the compiler and the series of physico-chemical tests conducted at the time, as well as regulations, methods and principles per the regulatory information noted in Section 15 herein. Should additional, supporting, or contrary information be identified to that which is contained herein, Talbot and the contact person noted in Section 1 must be informed immediately. The observations and recommendations made herein, and any other information or statements contained in this SDS must be applied with common sense. A precautionary, or minimum requirement, approach should be adopted in terms of all measures contained herein. This SDS is not a substitute for appropriate communication and training in terms of the hazards of the substance or mixture in question, nor the safe and legal handling, storage, transportation, and disposal. This SDS is not a toxicological study, standard operating procedure, risk assessment, license for handling, storage, transportation, or disposal of any substance or mixture, or a waste manifest. The developer of the waste pack compiler N.Hart, SDS author, and Talbot (Pty) Limited accept no liability whatsoever associated with the generation or use of this SDS or the information, observations, statements, or recommendations made herein. End of SDS.